

## EL-2000B

### 600TVL 2.8-12mm Motorized Zoom 150 ft IR Bullet

- 1/3" I-Sniper PIXIM DPS image sensor
- 690HTVL / 960H Effective Pixel
- Motorized Lens Control With Built in Button for local control
- RS-485 for remote control through DVR
- Wide Dynamic Range
- Intelligent IR Image Compensation
- IP67 Weatherproof
- Up to 150ft IR True Night Time Viewing

## Product Overview



### Head Office

IC Realtime  
3050 N Andrews Ave AXE  
Pompano Beach,  
FL 33064

Tel: 1 (866) 997-9009  
Fax: 1 (954) 827-5900  
Email: [Info@icrealtime.com](mailto:Info@icrealtime.com)  
Web: [www.icrealtime.com](http://www.icrealtime.com)

### West Coast Office

IC Realtime  
14180 West Van Buren St.  
Suite B105  
Goodyear, AZ 85338

Tel: 1 (602) 910-3432  
Fax: 1 (602) 626 3545  
Email: [west@icrealtime.com](mailto:west@icrealtime.com)  
Web: [www.icrealtime.com](http://www.icrealtime.com)

## EL-2000B

### 690TVL I-Sniper PIXIM DPS WideLux Vari-focal Bullet Camera

Imager / Electrical	
Image Sensor	1/3" I-Sniper PIXIM DPS
Effective Pixels	410,000 pixels 758(H)x540(V)
H.Resolution	690HTVL
Synchronization	Internal
Scanning System	2:1 Interlaced
Video Output	1.0Vp-p Composite. 75 Ohms
S/N Ratio	50 dB (AGC off, Weight ON)
Minimum Illumination	0 Lux
Shutter Speed	1/25s ~ 1/30, 720s (Global Shutter)
Gamma Correction	0.45
White Balance	2,000 ~ 11,000 K Auto ATW/AWB selectable by OSD
Gain Control	Standard: -6dB ~ 34dB Auto/Maximum by OSD
Smear Effect	0.01%
Power / Physical / Environmental	
Power	12VDC (210mA (IR Off) 630mA (IR On))
	24VAC (110mA (IR Off) 250mA (IR On))
Lens standard	2.8-12mm Varifocal Motorized lens (F1.4)
Viewable Distance	Up to 150' in 0 lux
MTBF of IR	20,000 hours
Iris control	DC Iris
Operating Temp	-14 - 122 F (-25 - 50 C) 90% RH
Dimensions	4.33" x 5.43" x 10.72"
	110mm x 138mm x 272.3mm
Weight	5.51lb or 2.5kg or 88.18oz