

IH-D7210

7-Inch Touch LED Screen Network Intercom System



This indoor intercom station makes client safety a priority. It features a 7" touch screen and two-way audio so that visitors can be vetted before being granted entry. The snapshot function and the ability to make emergency calls directly from the unit add layers of safety and convenience. For best results, pair this unit with our IH-C6260 outdoor station.

Features

- 7" TFT LCD touch screen, 800×480 resolution
- 1 channel 10/100Mbps self-adaptive Ethernet
- Device-to-device calling
- Snapshot function
- Emergency call function
- Multiple outdoor station connection
- PoE power supply
- SD card storage

IH-D7210

Specifications

| | |
|------------------------|---|
| Model | IH-D7210 |
| System | |
| Main Processor | Built-in microcontroller |
| Operating System | Embedded LINUX |
| Video | |
| Compression | H.264 |
| Resolution | 800x480 |
| Audio | |
| Input | All-direction Microphone |
| Output | Embedded loudspeaker |
| Bi-directional Talk | Supported |
| Display | |
| Size | Color 7-inch TFT LCD |
| Operating Modes | |
| Input | Mechanical keys(emergency, protection, video talk, monitoring,unlock), Touch screen technology |
| Alarm | |
| Input | 8 channels |
| Network | |
| Ethernet | 10 M / 100 Mbps adaptive |
| Network Protocol | TCP/IP |
| General | |
| Power | DC 10~15V or supply directly by Special switching power |
| Power Consumption | Standby: ≤ 1.5W, work: ≤ 7W |
| Working Environment | 14°F ~ 130°F/-10°C ~ 55°C / 10~90%RH / 86~106kpa |
| Dimensions (LxWxT) | 10.34"x7.15"x0.63"/262.6mmx181.6mmx16.1mm |
| Weight | 2.2lb ~ 1.0Kg |